

GROUND SWEEPING

- Collecting bucket
- Polypropylene brush
- Attachment to the machine
- Extremely tough and rugged



SWEeper BUCKET HD



- Direct drive motor
- Brushes made of PPN Ø550 mm
- HB400 steel reversible screwed cutting edge and bottom reinforcements
- Works in forward and reverse gear

SWEeper BUCKET D



- Brushes made of PPN Ø590mm
- N. 2 Ø250x50mm support wheels
- Mechanical working angle adjustment
- Hydraulic opening and closing of the collection bucket
- Works in forward gear
- Hooks for: forklift truck, tractor, earth moving machines
- Suitable for skid loaders, forklift trucks, telehandlers, compact wheel loaders

SWEeper BUCKET DS



Ø660 mm polypropylene brush

N. 3 Ø250x60mm support wheels

Internal hydraulic drive

Mechanical working angle adjustment

Hydraulic opening and closing of the collection bucket

Works in forward gear

Hooks for: forklift truck, tractor, earth moving machines

Suitable for telehandlers, backhoe loaders, wheel loaders from 90 hp to 170 hp

SWEeper BUCKET C



Ø750 mm polypropylene brush

N. 3 Ø405x110mm support wheels

Internal hydraulic drive

Mechanical working angle adjustment

Hydraulic opening and closing of the collection bucket

Works in forward gear

Hooks for: forklift truck, tractor, earth moving machines

Suitable for wheel loaders from 180 hp.





DIMENSIONS

| | | BS 210 C | BS 240 C | BS 280 C |
|---|---------------|----------|----------|----------|
| A | Width | 2360 | 2660 | 2990 |
| B | Depth | 2230 | 2230 | 2230 |
| C | Height | 1200 | 1200 | 1200 |

The Sweeper Bucket M3 series C is suitable for the cleaning of pavings and courtyard areas of industrial plants.

It can be fitted to any type of wheelloaders, backhoe loaders and telehandlers and is equipped with collecting bucket hydraulic operated, PPN brush Ø 750 mm, hydraulic hoses, no. 3 support wheels 405x110 mm, integrated motor, self-leveling attachment (optional) and mechanical working angle adjustment.

OPTIONALS

| | | |
|--|--|---|
| | Overflow valve | Extra strong wheels Ø 410x145 mm |
| Side brush right or left Ø 750 mm in PPN and STEEL | Solenoid valve kit to operate the hydraulic adjustment (if the machine is not equipped with 2 hydraulic lines) | Hydraulic working angling adjustment (an additional hydraulic line is required) |
| Water tank 200 l with electric pump and nebulizers | Water tank 400 l with electric pump and nebulizers | Nebulizer kit (without tank) |



| MODEL | BS 210 C | BS 240 C | BS 280 C |
|--|----------|----------|----------|
| Working width [mm] | 2100 | 2400 | 2800 |
| Working width with 20° angle [mm] | 1950 | 2250 | 2550 |
| Required oil flow (for 160bar) [l/min] | 56 | 56 | 56 |
| Ø Brush [mm] | 750 | 750 | 750 |
| Weight with collecting bucket [kg] | 795 | 904 | 957 |
| Capacity of collecting bucket [kg] | 450 | 480 | 550 |

